

**BILL OF QUANTITY FOR THE WORK OF "Renovation of Civil and Furniture work in
General Physics Lab, 1st Floor of Lake View Building, IACS"**

Sl. No.	Description of Items	Unit	Quantity	Rate/Unit (Rs.)	Amount (Rs.)
1	Wood work for frame structure making partition wall fitted and fixed in position complete including a protective coat of primer painting.	Cu.M	0.035		
2	Supplying, fitting and fixing boiling water proof 12mm thick ply conforming to IS: 710-1977 bonded with phenol formaldehyde synthetic resin conforming to IS: 848-1974 of approved make and brand fitted and fixed as per design as per approval and direction of Engineer-in-Charge.	Sq.M	5.70		
3	Priming one coat on timber or other plastered surface with Synthetic oil bound primer of approved quality including smoothening surface by sand papering etc.	Sq.M	5.70		
4	Painting on timber surface with best quality synthetic enamel paint of approved make and brand including smoothening surface by sand papering etc. including using of approved putty etc. on the surface, if necessary.	Sq.M	5.70		
5	Providing and fixing anodized Aluminium work of approved shade for fixed partition as per approved design using extruded standard sections of HINDALCO conforming to IS: 733 and IS: 1285, anodized colour of approved shade according to IS: 1868 fixed with rawl plugs and screws or with fixing clips including necessary filling up of gaps at junction, at top, bottom and sides with required neoprene felt etc.. This item will include all necessary standard accessories like P.V.C weather gasket, EPDM glazing gasket, handle, hinges and applying polysulphide sealant all round peripheri of the window, along with 5mm thick tinted float glass/frosted glass approved colour all complete.	Sq.M	7.75		
6	Providing and fixing anodized Aluminium work of approved shade for fixed Sliding Door as per approved design using extruded standard sections of HINDALCO conforming to IS: 733 and IS: 1285, anodized colour of approved shade according to IS: 1868 fixed with rawl plugs and screws or with fixing clips including necessary filling up of gaps at junction, at top, bottom and sides with required neoprene felt etc.. This item will include all necessary standard accessories like P.V.C weather gasket, EPDM glazing gasket, handle, hinges and applying polysulphide sealant all round peripheri of the window, along with 5.5 mm thick tinted float glass/frosted glass approved colour all complete. The rate is inclusive all door fittings and fixture like door handle, lock and other silding arrangement.	Sq.M	2.50		
7	Providing and fixing of Polyester film (dark black frosted range) of approved make and brand on aluminium partitions and sliding door as per design and instruction of EIC.	Sq.M	10.00		

Sl. No.	Description of Items	Unit	Quantity	Rate/Unit (Rs.)	Amount (Rs.)
8	Providing, Making and fixing of Wooden Instrument table, 3100mm long, 600mm width with 900 mm height as per attached drawing. Total construction made of 19mm thick water proof block board, having two intermediate supports. All four supports are double layers 19mm thick water proof block board. All visible surfaces to be finished with 1mm thick matt finished laminate of approved colour and make. All the free edges of the block board covered with 5mm thick wood beading including melamine finish. The inside surfaces to be finished with french polish. The top surface to be fixed with black granite (15 to 18 mm thick) using proper adhesive (as per instruction of EIC) with round moulding all the edges.	Each	1.00		
9	Providing, Making and fixing of Wooden Instrument table, 1500mm long, 600mm width with 900 mm height as per attached drawing. Total construction made of 19mm thick water proof block board having one intermediate supports. All three supports are double layers 19mm thick water proof block board. All visible surfaces to be finished with 1mm thick matt finished laminate of approved colour and make. All the free edges of the block board covered with 5mm thick wood beading including melamine finish. The inside surfaces to be finished with french polish. The top surface to be fixed with black granite (15 to 18 mm thick) using proper adhesive (as per instruction of EIC) with round moulding all the edges.	Each	3.00		
	TOTAL (Including all GST)				

Signature and Date of the Bidder